

Xperience

42xq series



Whether you're a business owner, consultant or installer, you'll find Carrier's 42XQ series console/underceiling air-conditioner perfect for your needs. Equipped with sophisticated features and designed to impress, the compact and aerodynamic 42XQ series will take you to new heights of cooling power and comfort.

- High Performance & Energy Efficiency
- Low Noise Level
- Indoor Air Quality Features
- Effective Air Distribution
- Aerodynamic Design
- Quick and Easy Installation & Management
- Sophisticated features & functions



Experience

42xq series

High Performance and Energy Efficiency

Can be matched with Carrier R-22 Condensing Units (up to 13 SEER)

Low Noise Level

Pressure level as low as 41dB(A) at low fan speed

Indoor Air Quality Features

- Fresh Air Intake option
- Optional combination of electrostatic, photocatalyzer and activated carbon filters to provide cleaner, fresher air for healthier living. Effectively traps and remove microscopic dust particles, clean pollutants from the air and remove unpleasant odors

Effective Air Distribution

Multi directional air distribution with 6 step vane control, auto swing and fan speed

Aerodynamic Design

Stylish and slim design perfectly complements any modern residence, office or business

Quick and Easy Installation & Management

- Easy clean design with one-step filter removal
- Clip-on concept on mounting components for ease serviceability
- Common components for all sizes
- Easy accessible parts for faster servicing

Sophisticated Features & Functions

- Euro-remote control with auto restart, self diagnostic, night set back and 24 hour timer
- Optional Condensate drain pump (field mounted inside the unit)

Technical specifications

	42XQ020	42XQ025	42XQ030	42XQ040	42XQ050	42XQ060
Model indoor	42XQ020	42XQ025	42XQ030	42XQ040	42XQ050	42XQ060
Capacity Btu/hr	20,000	24,000	30,000	36,000	52,000	60,000
Power V-Ph-Hz	230/1/60					
Weight (kg)	23	23.5	26.1	27.2	37.6	40.1
Dimension WxHxD (mm)	1020 x 232 x 625		1200 x 232 x 625		1650 x 232 x 625	
Sound (lo/hi) Pressure-dB(A)	43/47	41/48	46/49	45/48	45/48	45/48
Piping Connection	Suction inch	5/8	5/8	3/4	3/4	3/4
	Liquid inch	3/8				
Fan Blowers	Drive Type	Direct Driven				
	Quantity Used	2		3		4
	Tested -high Airflow -med (cfm) -low	580 550 510	650 600 550	720 660 600	790 720 600	1000 950 900
Controls	42XQ - Std standard	IR (Wireless) Control				
	42XQA optional	CRC (Wired) Control				
	Air Filter Type Standard	Washable Anti-Mold				
Optional	Air Filter	Electrostatic, photocatalytic and carbon activated filter				
	Pump	Condensate drain pump				



38CKC/N2AE
10 SEER



24ABR
13 SEER