



HI WALL 50 Hz



Features:

R-410A
REFRIGERANT

- Automatic Operation
- Cooling
- Dehumidify
- Fan
- Normal Sleep Mode
- Vertical Auto Swing
- Auto Fan
- I Feel
- Cold Plasma
- Timer
- Auto Restart
- Turbo
- Clock
- LED Display
- Turbo Cooling
- Low Voltage Startup
- Standby

TECHNICAL SPECIFICATIONS						
Indoor Unit Model			CH43CX009-H7H1H	CH43CX012-H7H1H	CH43CX018-H7H1H	CH43CX024-H7H1H
Outdoor Unit Model			CG43CX009PH7H1H	CG43CX012PH7H1H	CG43CX018PH7H1H	CG43CX024PH7H1H
Power Supply	Rated Voltage	V -	220-240	220-240	220-240	220-240
	Rated Frequency	Hz	50	50	50	50
	Phases	-	1	1	1	1
Cooling Capacity	Btu/h	9000	12000	17981	22000	
Min. Cooling Capacity	Btu/h	1500	2000	5732	8530	
Max. Cooling Capacity	Btu/h	11000	14000	19210	23202	
Rated Current	A	6.3	6.9	10.86	11	
EER	W/W	3.21	3.21	3.21	3.21	
Air Flow Volume	CFM	330/288/253/194	353/318/271/194	500/471/412/335	647/588/559/500	
Indoor Unit	Sound Pressure Level	dB (A)	39/36/32/28	41/37/33/29	47/43/39/35	46/44/40/36
	Sound Power Level	dB (A)	52/49/45/41	54/50/46/42	57/53/49/45	58/56/52/48
	Dimension (W×H×D)	inch	31.102×10.827×7.874	33.268×11.378×8.228	38.189×11.811×8.819	42.441×12.795×9.685
	Dimension of Carton Box (L×W×H)	inch	33.976×10.551×13.858	36.142×10.945×14.331	40.866×14.961×12.008	45.079×16.142×13.189
	Dimension of Package(L×W×H)	inch	34.094×10.669×14.449	36.26×11.063×14.921	40.984×15.079×12.598	45.197×16.26×13.78
	Net Weight	lb	19.8	24.3	29.8	35.3
	Gross Weight	lb	24.3	28.7	36.4	43.0
Outdoor Unit	Cooling Operation Ambient Temp. Range	°C / °F	18-43 / 64.4-118	18-43 / 64.4-118	18-43 / 64-109	18-48 / 64-118
	Sound Pressure Level	dB (A)	49	51	54	56
	Sound Power Level	dB (A)	62	64	64	68
	Dimension (W×H×D)	inch	27.953×21.654×12.52	27.953×21.654×12.52	35.394×23.465×14.882	37.598×27.559×15.591
	Carton Box Dimension (L×W×H)	inch	30.354×13.701×23.307	30.354×13.701×23.307	37.205×16.417×24.803	40.394×17.913×28.937
	Package Dimension (L×W×H)	inch	30.472×13.819×23.898	30.472×13.819×23.898	37.323×16.535×25.394	40.512×18.031×29.528
	Stacked Layers	-	5	5	4	4
	Net Weight	lb	60.6	65.0	88.2	99.2
	Gross Weight	lb	65.0	69.5	95.9	110.2
	Refrigerant		R410A			
	Refrigerant Charge	kg/ oz	0.74/ 26.10	1.0/ 35.27	1.20/ 42.3	1.35/ 47.6
Connection Pipe	Max Distance Height	m/ ft	10/ 32.8	10/ 32.8	10/ 32.8	10/ 32.8
	Max Distance Length	m/ ft	15/ 49.2	20/ 65.6	15/ 49.2	25/ 82.0
Loading Quantity	20' Container	unit	114	108	75	55
	40' Container	unit	234	225	156	118
	40' High Cube Container	unit	270	261	179	131



Carrier InterAmerica Corporation
Miami, Florida USA
www.ciac-comfort.com

Authorized Dealer:

CG/CH43CXP7/SL