



Turn to the experts



SUPER SLIM CASSETTE

Compact Design, Super Slim Body Size with External Duct Capability feature





- ➔ **360° Airflow Panel is standard**
- ➔ **Fresh Air In-take**
- ➔ **Remote Control**
- ➔ **Compact Design, Super Slim Body Size**
- ➔ **External Duct Capability feature**

MODEL NUMBER		42KUQ036N-1	42KUQ060N-1
PANEL CODE		22012900002930	22012900002930
Power supply	V- Ph-Hz	220-230V, 1Ph. 60Hz	220-230V, 1Ph. 60Hz
Fan motor	Nominal Cooling Capacity	Btu/h	36000
	Model		YKT-65-6-3
	Speed (Hi/Mi/Lo)	r/min	620/490/410
Air flow (Hi/Mi/Lo)	m3/h	1785/1432/1192	1992/1688/1454
Air flow (Hi/Mi/Lo)	CFM	1050.00/842.35/701.18	1171.76/992.94/855.29
Noise level (Hi/Mi/Lo)	dB(A)	52.7/47.8/44.9	53.4/49.9/47.7
Throttle type		/	Throttle valve
Indoor unit	Dimension (W*D*H) (body)		830x830x245
	Dimension (W*D*H) (body)	inch	32.68x32.68x9.65
	Packing (W*D*H) (body)	mm	910x910x290
	Packing (W*D*H) (body)	inch	35.83x35.83x11.42
	Dimension (W x Dx H) (panel)	mm	950x950x55
	Dimension (W x Dx H) (panel)	inch	37.40x37.40x2.17
	Packing (W x Dx H) (panel)	mm	1035x1035x90
	Packing (W x Dx H) (panel)	inch	40.75x40.75x3.54
	Net/Gross weight (body)	kg	26.4/30.5
	Net/Gross weight (body)	lb	58.20/67.24
	Net/Gross weight (panel)	kg	6/9
Drainage water pipe dia	mm	ODΦ25mm	/
Qty'per 20' /40' /40'HQ	Indoor Unit	96/208/234	84/182/208
Thermostat type		Remote Control	Remote Control

Authorized Dealer



Turn to the experts