




Confíe en los Expertos



DUCTED FAN COIL UNIT

Efficiency and comfort enhancing fan coils designed for years of reliable operation





Product Model			42KUT036N-1	42KUT060N-1
Power supply		V- Ph-Hz	220-230V,1Ph, 60Hz	220-230V,1Ph, 60Hz
Indoor fan motor	Model		YKSS-115-4-21	YKSS-480-4-2
	Input	W	253.0	/
	Capacitor	uF	8	9.5
	Speed(Hi/Mi/Lo)	r/min	1150/990/870/760	12010/1040/900/800
Indoor coil	Number of rows		3.0	4.0
	Tube pitch(a)x row pitch(b)	mm	21x13.37	21x13.37
	Fin spacing	mm	1.4	1.4
	Fin type (code)		Hydrophilic aluminum	Hydrophilic aluminum
	Tube outside dia.and type	mm	Φ7,Inner groove tube	Φ7,Inner groove tube
	Coil length x height x width	mm	915x294x40.11	1030x378x53.48
	Number of circuits		7	8
Indoor air flow (Hi/Mi/Lo)		m3/h	1725/1193/991	2604/2180/1885
Indoor noise level (Hi/Mi/Lo)		dB(A)	/	/
ESP	Rated	Pa	37	50
	Range	Pa	0-160	0-160
Indoor unit	Dimension(W*D*H)	mm	1100/774/249	1200/874/300
	Packing (W*D*H)	mm	1305/805/315	1405/915/365
	Net/Gross weight	kg	33.7/41	48.8/57.9
Drainage water pipe dia		mm	ODΦ25mm	ODΦ25mm
Qty' per 20' /40' /40'HQ		Indoor unit	77/161/198	62/130/149
Refrigerant piping	Liquid side/ Gas side	mm(inch)	9.52mm(3/8in)/19mm(3/4in)	9.52mm(3/8in)/19mm(3/4in)

Authorized Dealer



Turn to the experts

Ref: 102024