



Confíe en los Expertos



SUPER SLIM CASSETTE

Compact Design, Super Slim Body Size with External Duct Capability feature





- ➔ **360° Airflow Panel is standard**
- ➔ **Fresh Air In-take**
- ➔ **Remote Control**
- ➔ **Compact Design, Super Slim Body Size**
- ➔ **External Duct Capability feature**

Product Model			42TNC0362002302	42TNC0482002302-1	42TNC0602002301
Power supply		V- Ph-Hz	220-230V,1Ph, 60Hz	220-230V,1Ph, 60Hz	220-230V,1Ph, 60Hz
Indoor fan motor	Model		YKS-125-6-6	YKS-125-6-6	YKS-125-6-6
	Input	W	242.0	242.0	242.0
	Capacitor	µF	4.5	4.5	4.5
	Speed(Hi/Mi/Lo)	r/min	780/600/550	780/600/550	780/600/550
Indoor coil	Number of rows		2.0	3	3
	Tube pitch(a)x row pitch(b)	mm	21x13.37	21x13.37	21x13.37
	Fin spacing	mm	1.4	1.4	1.4
	Fin type (code)		Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum
	Tube outside dia.and type	mm	Φ7,Inner groove tube	Φ7,Inner groove tube	Φ7,Inner groove tube
	Coil length x height x width	mm	2010x210x26.74	2080x252x40.11	2080x252x40.11
	Number of circuits		10	12	12
Indoor air flow (Hi/Mi/Lo)		m3/h	1673/1189/1065	1800/1600/1400	1800/1600/1400
Indoor noise level (Hi/Mi/Lo)		dB(A)	/	52.1/44.4/42.5	52.1/44.4/42.5
Indoor unit	Dimension(W*D*H)(body)	mm	840x840x245	840x840x287	840x840x287
	Dimension (W x Dx H)(panel)	mm	950x950x55	950x950x55	950x950x55
	Packing (W*D*H)(body)	mm	900x900x265	900x900x307	900x900x307
	Packing (W x Dx H)(panel)	mm	1035x1035x90	1035x1035x90	1035x1035x90
	Net/Gross weight(body)	kg	25.8/30.3	30.4/35.3	30.4/35.3
	Net/Gross weight(panel)	kg	6.5/8	6.5/8	6.5/8
Drainage water pipe dia		mm	ODΦ25mm	ODΦ25mm	ODΦ25mm
Qty' per 20' /40' /40'HQ		Indoor unit	128/268/294	100/212/238	100/212/238
Refrigerant piping	Liquid side/ Gas side	mm(inch)	9.52mm(3/8in)/19mm(3/4in)	9.52mm(3/8in)/19mm(3/4in)	9.52mm(3/8in)/19mm(3/4in)

Authorized Dealer



Turn to the experts